

IMPACT-302T



Salient Features

- ♦ **Pairing**
Any transmitter & receiver can be paired on-site (for easy spare management)
- ♦ **Adjustable Range**
Operating Range Adjustment (from 10m to 100m)
- ♦ **Adjustable Start Range**
Only START functionality can be range adjustable
- ♦ **Password**
Transmitter password protection
- ♦ **Frequency Change**
Operating channel can be changed on site
- ♦ **Idle Time**
Configurable Idle Time out in Transmitter

Additional Features

Emergency STOP	2 NC contacts for EMS (EN-954-1 Safety Standard)
Indication	LED Indication for Battery LOW, Transmission and Error status
Address Code	Unique Address Code to avoid interference
Antenna	Internal Antenna in transmitter & receiver
Relay Assignment	Configurable Relay assignment available

Transmitter

Operating Frequency	433-434 MHz
Channel Spacing	25 KHz
Modulation	FM (4GFSK/2GFSK)
RF Power Output	10 mW
Power Consumption	18 mA (Unidirectional)
Standby Power Consumption	1 mA
Battery Capacity and Type	2 nos, AA size Alkaline, 3.0V
Operating Temperature	-20°C to +70°C
Weight	350 gms (without battery)
Dimensions (mm)	205 (H) X 75 (W) X 45 (B)
Operating Range	100 meters
Protection Rating	IP 65 IS/IEC 600529:2001

H. O. Unit - I : C-15/16, Nand Jyot Industrial Estate, Andheri-Kurla Road, Mumbai - 400072,
Tel : (022) 42469700-30
E-mail : sales@socgroup.in

Unit - II : Plot No. 4912, G. I. D. C., Phase IV, Vatva, Ahmedabad - 382445
Tel.: (079) 400832 01/2/3/4,
E-mail : sales.amd@socgroup.in



Technical Specification

Number of commands in Transmitter unit	Upto 12 + Start/Stop + Alarm
CRC	32 Bit
Response Time	<50 ms
Active Emergency Response Time	<50 ms
Passive Emergency Response Time	1900 ms

Receiver

Operating Frequency	433-434 MHz
Channel Spacing	25 KHz
RF Sensitivity	-117dBm at 0.6kbaud
Number of Relays	Upto 21 + 2 (Start/Alarm)
Relays	Resistive load: 5A at 250VAC
Power Requirements	110 VAC / 230 VAC
Fastening	By means of Nuts & Bolts
Operating Temperature	-20°C to +70°C
Weight	Approx 1.40 Kg
Dimensions (mm)	282 (H) x 220 (B) x 110 (W)
Operating Range	100 meters
Protection Rating	IP 65

SPEED-O-CONTROLS PVT. LTD.
RADIO REMOTE CONTROLS

Visit us at :
www.speedocontrols.com
www.socremote.com